
NICOPRESS SLEEVE (REF)
AN100-3 (REF)
3415D-2 (REF)
4.00
A
A
B
B
SPACER IF REQ'D (4237B-1&-3)
3410B-8
SWIVEL
REPLACE EXISTING
BOLT WITH AN6-32A ③
USE EXISTING NUT,
AN960-C-616 AS REQ'D ④
AN5-23A
AN365-524
AN960-516
IMPRESSION STAMP
SERIAL NO. LOCATION
R.H. SIDE
3409D-2 RELEASE
ASSEMBLY
3409D-4 SPACER
AN5-22A
AN365-524
AN960-516
REMOVE SPACERS ON
INSIDE OF 3409D-2
ASSY FOR INSTALL.
WITH 1.50 WIDE TAIL
WHEEL SPRING


ROLL NAME PLT
TO FIT TUBE
1A314-1
DRILL #52 (.0635)
(2) PLACES FOR
#2x3/16 TYPE U
P.K. SCREWS

SECTION B-B
R.H. TUBE



SECTION A-A

MS 21919DG5 CLAMP ②
ATTACH BY USING
EXISTING BOLT

NOTE:

1. REDRAWN TO USE 3409D-2 REL. ASSY.
2. PROOF TEST REQ'D
   - (A.) MAX. OF 60# RELEASE LOAD ALLOWABLE FOR A STATIC LOAD OF 600# ON HOOK
   - (B.) MIN. OF 4# TO RELEASE WITH NO LOAD ON HOOK
   - (C.) MAX. OF 10# TO RELEASE WITH NO LOAD ON HOOK
3. CHG 'C' - ① AN6-26A TO AN6-32A USE EXISTING NUT, AN960-C-616 AS REQ'D.
   ② AN742-7 TO MS21919DG5 CLAMP. ③ AN6-26A TO: AN6-32A
   ④ ADD AN960-C-616 WASHER.

NO. PER ASSY.	ASSEMBLY	PART NO.	PAR. NAME	STOCK SIZE	MATERIAL	SPECIFICATION	HEAT TREAT	U.T.S. P.S.I.	FINISH	UNIT WT.
2		#2x3/16	P.K. SCREWS	TYPE U PLATED						
A/R		AN960-C616	WASHER							
2		AN960-516	WASHER							
2		AN365-524	NUT							
1		AN6-32A	BOLT							
1		AN5-23A	BOLT							
1		AN5-22A	BOLT							
1		MS21919DG5	CLAMP							
1		1A314-1	NAME PLATE							
1		3410B-8	SWIVEL							
1		3409D-4	SPACER							
1		3409D-2	TOW REL. SUPPORT							
		3408D-1	TOW REL. ASSY							

THIS PRINT WILL NOT BE KEPT UP TO DATE

LET.	CHANGE	SERIAL	DATE	BY	APP.
C	INC. E.C.O. S-68	1756	4-25-68	AH	
B	SEE NOTE 1	1018UP	3-13-64	WEF	

MODEL	REQ'D	ASSEMBLY

LIMITS UNLESS OTHERWISE SPECIFIED

ANGULAR	FRACTIONAL	DECIMAL

REPLACES	REPLACED BY
3408D DATED 1-22-57	

APP.		
LOFT		
PR. ENG.		
STRESS		
CHECKED	ES	12-11-
DRAWN	WEF	3-13-64

CLASSIFICATION

[redacted]

SCALE	OPP. HAND
FULL	

SCHWEIZER AIRCRAFT CORP.
ELMIRA, NEW YORK

TOW RELEASE ASSY
SUPER CUB

3408D

REV. C

SEP 9 - 1977